


# LED DOWN LIGHT COB CORONE (SQ/RO)



## Specifications

<b>Model</b>	CORONE
<b>Input power</b>	6W, 9W, 16W, 24W, 30W, 40W, 50W
<b>Cut out Dimension</b>	64mm, 64mm, 86mm, 100mm, 120mm, 120mm, 120mm
<b>Input voltage</b>	100-285 Vac
<b>Frequency</b>	47-55Hz
<b>Power Factor(pf)</b>	>0.65
<b>Thd (%)</b>	<15
<b>Driver Efficiency (%)</b>	>85
<b>Led Type</b>	LEDTEEN (Chip - Bridgelux)
<b>Lumen</b>	600lm, 900lm, 1600lm, 2400lm, 3000lm, 4000lm, 5000lm
<b>Driver Type</b>	Constant Current
<b>Light Efficiency (lm/W)</b>	>85
<b>CCT</b>	2700, 4000, 6500 (+/-10%)
<b>Led Life Time (hrs)</b>	50000 hrs
<b>CRI (Ra)</b>	≥80
<b>Housing (body)</b>	Aluminium Diecast with Powder Coating
<b>Optical Cover</b>	Transparent
<b>Beam Angle</b>	24° - 38° - 60°
<b>Working Temperature</b>	-15°C to 55°C
<b>IP Grade</b>	IP20